



**ROOFING  
PRODUCTS**

153 BOWLES ROAD  
AGAWAM, MA 01001

413-789-0252

800-633-3800

FAX: 413-789-1069

WWW.OLYFAST.COM

## **PRESS RELEASE**

**RELEASE:** Immediate

**CONTACT:** Sam Everett  
Channel Marketing Manager  
(800) 633-3800 x 419  
severett@olyfast.com

### **OMG Introduces Height Adjustable Strut Model PipeGuard**

**Agawam, Mass., July 1, 2010** – OMG has introduced the Height Adjustable Strut Model PipeGuard for applications requiring support for multiple small pipes in one location.

Diverse and flexible, the Height Adjustable Strut Model PipeGuard can be used for a wide range of small roof-top pipe applications including gas and refrigeration lines, electrical and solar conduit as well as HVAC lines. The system is compatible with PVC, copper, cast iron and most other pipe materials, and is adjustable to heights from 5- to 10-inches, with custom heights available.

As with the other PipeGuard units, the Height Adjustable Strut Model has a wide base for maximum stability and is fast and easy to install. The heavy duty EPDM rubber base will not damage roofing covers and helps to dampen pipe motion due to vibration. The new Height Adjustable Strut Model PipeGuard includes a 1 5/8-inch galvanized strut channel that accommodates standard pipe support clamps (sold separately at most hardware, plumbing or electrical supply stores). Each unit will support up to 160 lbs.

“OMG PipeGuard is a safe alternative to traditional pressure treated wood blocks that can rot, splinter and damage the roofing system,” said Dan Genovese, product manager for OMG. “In addition, the simple design is easy to use and install.”

Each unit is 10-inches long by four-inches tall and will support several pipes depending on their diameter. In addition, Height Adjustable Strut Model PipeGuard units will not deteriorate from water or sunlight exposure so there’s nothing to break down or damage the roofing system.

Height Adjustable Strut Model PipeGuard units are packaged 5 to the carton, come fully assembled and are immediately available through OMG’s extensive commercial roofing distribution network. Field support is provided by the OMG field sales network, along with nationwide, toll-free telephone support.

OMG PipeGuard units are available in seven sizes and will accommodate roof-top pipes and conduit up to 5-inches in diameter. For additional information, visit [www.olyfast.com](http://www.olyfast.com) or call (800) 633-3800 or email [info@olyfast.com](mailto:info@olyfast.com).

# # #